

COSMOS ALUMINIUM A.E. — 8th km National Road Larissa - Athens 41110 Larissa, P.O. Box 1379 — Greece — T: +30 2410 567567 www.cosmosaluminium.com - VAT EL 998789236





## Inspection certificate 3.1

According to: EN 10204:2004

Customer:	A + A Pardubice spol. s r.o.
-----------	------------------------------

Alloy/Temper:	EN AW-6060 / <b>T</b> 66	Cust. Order No:	OV-1368/19-833863
Profile Code:	050042	Description:	ASYM. <b>L</b> 100x30x3

The extruded products are in compliance with the requirements of the order. The stated values are representative for the profiles extruded and comply with the following European Standards:

i. Chemical composition and form of products according to:	EN <b>5</b> 73-3:2013
ii. Technical conditions for inspection and delivery according to:	EN <b>7</b> 55-1:2016
iii. Mechanical properties according to:	EN <b>7</b> 55-2:2016
iv. Tolerances on dimensions and form according to:	EN <b>7</b> 55-9:2008
v. Temper designation according to:	EN <b>5</b> 15:2017

1. Chemical Composition

EN ANY 5050	Si	Fe Cu	_	Mn	Mg	Cr	Zn	Ti	Other		
EN <b>A</b> W-6060			Cu						Each	Total	Al
Should be within:	0,30-0,60	0,10-0,30	0,10	0,10	0,35-0,60	0,05	0,15	0,10	0,05	0,15	Rest
Charge No: EA19D0296A	0,42	0,17	0,01	0,01	0,47	0,01	0,01	0,009	0,05	0,15	Rest

The chemical composition test results are obtained by the aluminium billet supplier. Traceability procedures are being operated and the corresponding inspection documents can be provided.

## 2. Mechanical Properties

Ir	nspection Date	Charge No:	Bundle Nr.	Profile	Alloy	Temper	Webster Hardness	Brinell Hardness	Tensile Strength Rm (N/mm²)	Yield Strength Rp 0.2 (N/mm²)	Elongation A%	
	4/7/2019	EA19D0296A	545139	050042	6060	T66	13	77	223	186	16,25	

The material hardness is tested after the heat treatment procedures. Traceability procedures are being operated and the corresponding inspection documents can be provided.

Mechanical properties as 755-2 indicated, are derived from tensile tests as per EN 6892:2016 and the number of specimens comply with the regulations described in EN 755-1.

COSMOS Aluminium

Venetia Ziarra Quality Production Executive